



CERTIFICATE OF PRODUCT CERTIFICATION

SOLAR PRODUCT CERTIFICATE

CERTIFICATE NO.: CQC23024373871

Valid from: Feb.07,2023

Valid until:long-term

NAME AND REGISTERED ADDRESS OF THE APPLICANT	SolaX Power Network Technology (Zhejiang) Co.,Ltd. No.288,Shizhu Road, Tonglu Economic Development Zone, Tonglu City, Zhejiang Province, 310000 P. R. CHINA
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	SolaX Power Network Technology (Zhejiang) Co.,Ltd. No.288,Shizhu Road, Tonglu Economic Development Zone, Tonglu City, Zhejiang Province, 310000 P. R. CHINA
NAME AND LOCATION OF THE FACTORY	SolaX Power Network Technology (Zhejiang) Co.,Ltd. No.288,Shizhu Road, Tonglu Economic Development Zone, Tonglu City, Zhejiang Province, 310000 P. R. CHINA
PRODUCT NAME, MODEL AND SPECIFICATION	Grid-Connected PV Inverter X3-PRO-17K-G2 , X3-PRO-20K-G2 , X3-PRO-25K-G2 , X3-PRO-30K-G2 (See Appendix)
THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS	NB/T32004-2018
TYPE OF CERTIFICATION SCHEMES	Type Testing of Product + Initial Factory Inspection + Follow up Factory Inspection

This is to certify that the above mentioned product(s) complies with the requirements of certification rules of CQC33-461239-2018.
The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body.

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE OF PRODUCT CERTIFICATION

SOLAR PRODUCT CERTIFICATE

APPENDIX

Page 1 of 1

CERTIFICATE NO.: CQC23024373871

PAPER:

X3-PRO-30K-G2

直流输入:MPPT 电压范围 160V-980Vdc,最大直流输入电压 1100Vdc,最大输入电流 32A*3;
交流输出: 3/N/PE, 220V/380V, 50Hz, 45.5A, 额定交流输出功率 30kW;

X3-PRO-25K-G2

直流输入:MPPT 电压范围 160V-980Vdc,最大直流输入电压 1100Vdc,最大输入电流 32A*3;
交流输出: 3/N/PE, 220V/380V, 50Hz, 41.8A, 额定交流输出功率 25kW;

X3-PRO-20K-G2

直流输入:MPPT 电压范围 160V-980Vdc,最大直流输入电压 1100Vdc,最大输入电流 32A*3;
交流输出: 3/N/PE, 220V/380V, 50Hz, 33.6A, 额定交流输出功率 20kW;

X3-PRO-17K-G2

直流输入:MPPT 电压范围 160V-980Vdc,最大直流输入电压 1100Vdc,最大输入电流 32A*2;
交流输出: 3/N/PE, 220V/380V, 50Hz, 27.5A, 额定交流输出功率 17kW。

NOTE: This appendix is valid when used with the certificate.



CHINA QUALITY CERTIFICATION CENTRE